



POLYCAB WIRES PVT. LTD.

Industrial Cables LP No. 04/2017-18 Dtd 1st September 2017

POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - FLAME RETARDANT (FR) CONFORMING TO IS-694:1990 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS

Size (sq.mm.)	FR							
	45 Mtr.	Coils Per Box	90 Mtrs.	Coils Per Box	180 Mtrs. (Box Packing)	Coils Per Box	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)	Coils Per Box
0.75	410	48	775	28			2585	10
1	530	36	1015	24	2030	12	3385	8
1.5	800	30	1520	16	3040	10	5065	6
2.5	1270	20	2420	12	4840	6	8070	4
4	1925	16	3665	8	7330	4	8145	4
6	2855	8	5435	6	10870	3	12080	3
10			9610	1			21355	1
16			15400	1			34220	1

POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL(MULTISTRAND) CABLES – FLAME RETARDANT LOW SMOKE (FRLSH) /FLAME RETARDANT ZERO HALOGEN (FRZH) / LOW SMOKE ZERO HALOGEN (LSZH) / HALOGEN FREE FLAME RETARDANT (HFFR) CONFORMING TO IS-694:1990 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS

Size (sq.mm.)	FRLS				HFFR/FRZH/LSZH	
	180 Mtrs. (Box Packing)	Coils Per Box	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)	Coils Per Box	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)	Coils Per Box
0.75			2735	10	2965	10
1	2125	12	3545	8	3865	8
1.5	3190	10	5315	6	5775	6
2.5	5085	6	8480	4	9230	4
4	7710	4	8570	4	9130	4
6	11370	3	12635	3	13460	3
10			22485	1	23950	1
16			36100	1	38460	1

Notes

1. The above rates are exclusive of GST which shall be charged extra.
2. This Price List is subject to change without notice.
3. As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance. The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.