

**POLYCAB WIRES PVT. LTD.**

Industrial Cables LP No. 06/2017-18 Dtd 2nd December 2017

POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES - FLAME RETARDANT (FR) CONFORMING TO IS-694:1990 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS

Size (sq.mm.)	FR							
	45 Mtr.	Coils Per Box	90 Mtrs.	Coils Per Box	180 Mtrs. (Box Packing)	Coils Per Box	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)	Coils Per Box
0.75	415	48	785	28			2615	10
1	535	36	1020	24	2040	12	3400	8
1.5	800	30	1525	16	3050	10	5085	6
2.5	1285	20	2450	12	4900	6	8165	4
4	1925	16	3665	8	7330	4	8145	4
6	2880	8	5490	6	10980	3	12200	3
10			9705	1			21570	1
16			15555	1			34570	1

POLYCAB PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL(MULTISTRAND) CABLES – FLAME RETARDANT LOW SMOKE (FRLSH) /FLAME RETARDANT ZERO HALOGEN (FRZH) / LOW SMOKE ZERO HALOGEN (LSZH) / HALOGEN FREE FLAME RETARDANT (HFFR) CONFORMING TO IS-694:1990 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS

Size (sq.mm.)	FRLS				HFFR/FRZH/LSZH	
	180 Mtrs. (Box Packing)	Coils Per Box	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)	Coils Per Box	300 Mtrs (0.75-2.5) 200 Mtrs (4-16)	Coils Per Box
0.75			2745	10	2800	10
1	2140	12	3570	8	3640	8
1.5	3210	10	5350	6	5460	6
2.5	5150	6	8585	4	8760	4
4	7700	4	8555	4	8725	4
6	11530	3	12810	3	13065	3
10			22650	1	23105	1
16			36300	1	37025	1

Notes

1. The above rates are exclusive of GST which shall be charged extra.

2. This Price List is subject to change without notice.

3. As per international practice which is also adopted by Bureau of Indian Standards, the diameter of the conductor shown above is nominal. The size of the conductor is determined by its resistance.

The construction of the conductor is as per market convention and should be treated as a guideline only. It may vary within the limits of IS 8130:1994 with its related classes and tables.